

# Hornady Lock-N-Load® Powder Measure Item #050069

## Hornady Powder Measure

**Kaliber:** Munition - Wiederladen

**Zustand:** neu

### Beschreibung:

**LARGEST CHARGE RANGE IN THE INDUSTRY** By simply changing rotor and inserts, you can use one Lock-N-Load® Powder Measure to load powders and charges from .5 grain to 265 grains. **MULTIPLE MOUNTING METHODS** Mount to your bench using a standard mounting bracket and lock ring, or use our Lock-N-Load® bushings to mount this versatile measure on the Fast Load Powder Measure Stand. **PUSH-BUTTON RELEASE FUNCTION** To change metering inserts, simply push the release button and change over to another metering insert. Verify the new charge and you're reloading again right away. Inserts can be swapped in seconds. Go from reloading 30-06 to 45 Auto in no time. Keep the preset inserts with your die sets. **ADJUSTABLE TENSION** The O-ring on the metering insert adjustment lets you put a slight amount of tension on the metering unit to make fine, incremental adjustments. Once you've set your charge, tighten the lock ring to secure the setting. **PRECISION TOLERANCE** With only .002" clearance between the drum and rotor, it's the tightest in the industry for a standard measure. This tight tolerance helps eliminate powder binding between the frame and drum, delivering smooth function with all types of propellant - extruded or ball. **SMALL AND LARGE DROP TUBE** These tubes speed up powder flow. Two drop tubes are included for .204 to 45 caliber. Use the largest drop tube that fits the case mouth. Optional 17 caliber drop tube sold separately. (No. 390709)

deutschlandweiter Versand +8,50€

120,00 EUR\*

\* inkl. MwSt.; zzgl. Versandkosten

## CORE-GUNS.COM

**Hornady  
Lock-N-Load  
POWDER  
MEASURE**



**WAFFEN | OPTIKEN | MUNITION | ZUBEHÖR**

### Anbieterinformationen

**Core Guns UG**

Sasbacherstr. 4  
68239 Mannheim  
Baden-Württemberg

**Telefon:**

06203 - 892727

**Mobil:**

06203 - 892727

**E-Mail:**

info@core-guns.com

**Webseite:**

www.core-guns.com